



NOYES® **CSM1 Contractor Series Optical Power Meter**

The NOYES CSM1 from AFL is a palm-sized, cost-effective optical power meter designed for measuring optical power in Premises, Telco, or Broadband fiber optic networks and for performing insertion loss measurements on multimode or single-mode fiber optic links. Weighing only 0.4 lb, this power meter is ideal for field use.

The CSM1 stores optical references for each calibrated wavelength and features multiple test Tone detection for fiber identification. A large LCD display with backlight shows measured power [dBm or μ W] or insertion loss [dB], calibrated wavelengths [nm], tone frequency [Hz], and indicates a low battery condition.

The CSM1 optical input port accepts a variety of NOYES thread-on style adapter caps (ordered separately) to meet a wide range of testing requirements. One adapter cap, 2.5 mm Universal, is included.

Being powered by two AA alkaline, the CSM1 offers a five-minute auto-off feature and over 300 hours of operation with backlight off.

The CSM1 is fully N.I.S.T. traceable.

Features

- Palm-sized, rugged, lightweight
- Multimode or single-mode applications
- 270, 330, 1000, 2000 Hz Tone detection
- Large LCD with backlight
- Power measurements in dBm or μ W; insertion loss in dB
- Reference power level storage
- Automatic power-off function
- Battery gauge
- Long battery life with 2 x AA alkaline
- Cost-effective, easy to use
- N.I.S.T traceable

Application

- Premises (Ge), Telco (InGaAs), and Broadband (+26 dBm) models
- Passive Optical Networks (PON) testing

NOYES®
CSM1 Contractor Series Optical Power Meter

Specifications ^a

OPTICAL	CSM1-1	CSM1-2	CSM1-3	CSM1-4
Calibrated Wavelengths	660, 780, 850 nm	850, 1300, 1310, 1550 nm	850, 1300, 1310, 1490, 1550, 1625 nm	850, 980, 1310, 1490, 1550, 1625 nm
Detector Type	Silicon (Si)	Germanium (Ge)	InGaAs	Filtered InGaAs
Measurement Range	+6 to -70 dBm	+6 to -60 dBm	+6 to -70 dBm	+26 to -50 dBm
Tone detect Range	+6 to -45 dBm	+6 to -50 dBm +6 to -45 dBm for 850 nm		+6 to -30 dBm +6 to -25 dBm for 850 nm
Accuracy ^b	±0.3 dB			
Resolution	0.01 dB			
Measurement Units	dB, dBm, µW			
GENERAL				
Power	2 x AA batteries			
Battery Life	>300 hours			
Operating Temperature	-10 °C to 5 °C, 90 % RH (non-condensing)			
Storage Temperature	-30 °C to 60 °C, 90 % RH (non-condensing)			
Size (H x W x D)	11.4 x 6.4 x 3.2 cm (4.5 x 2.5 x 1.3 in)			
Weight	0.18 kg (0.4 lb)			

Notes:

- a. All specifications valid at 25 °C unless otherwise specified.
- b. Accuracy measured at 25 °C and -10 dBm per N.I.S.T. standards.

Ordering Information

INCLUDES	AFL NO.
2.5 mm Universal adapter cap, 2 x AA batteries, user's guide, and carry case.	All CSM1 models

Authorized Channel Partner



United States
 Customer Service
 1.800.321.5298
 1.603.528.7780
 www.AFLglobal.com

Europe, Middle East, Africa
 Max Penfold
 Max.Penfold@AFLglobal.com
 +44 1799 542 840
 +44 7802 839 160

Middle East
 Ahmed El Sakaty
 Ahmed.ELsakaty@AFLglobal.com
 +20 106 451 523

Africa (Sub Sahara)
 Nicholas Cole
 Nicholas.Cole@AFLglobal.com
 +44 7702 005 590

Greater China
 Dai Liu
 Dai.Liu@AFLglobal.com
 +86 133 1101 4533

Asia-Pacific (non-China)
 Saw Biing Huei
 Biing.Saw@AFLglobal.com
 +65 9791 3398