

American  
**Polywater**<sup>®</sup>  
Corporation

# ZipSeal<sup>™</sup>

## Duct Sealant



- Seals out Water, Sewer Gases, and Rodents From Conduits
- Installs in 45 Seconds
- Easy to Re-Enter
- Holds up to 10' of Water-Head Pressure
- One Kit Seals Five 2" (50mm) Conduits
- Compatible with Cables and Conduits
- Complies with TIA-758-B Standard 5.1.1.2.8, 5.4.2.3 and 7.4.2.8.1 Sealing Ducts




### Open-Celled Canned Foams & Duct Putty


- Do Not Hold Water-Head Pressure
- Do Not Fully Cure in Conduits
- Sag and Dry Out Over Time

# Polywater® ZipSeal™ Duct Sealant

**ZipSeal™ Duct Sealant** is a practical and efficient way to seal innerducts and conduits. The revolutionary Zip-Disc insert and unique two-part foam installs quickly and effectively. This innovative design allows for horizontal and vertical installation with minimal drippage. The foam can be removed in just minutes. ZipSeal™ can hold up to 10 feet of water-head pressure.



Horizontal application



Vertical application

Cat. No.	Package Components	Case Qty
ZIP-50KIT1	1 50mL two-part foam sealant cartridge w/ resealing cap, 2 static mixing nozzles, 2 pairs disposable gloves 5 2" Zip-Discs	1
ZIP-50KIT1G	ZIP-50KIT1 w/ dispensing tool	1
ZIP-50KITB6	6 ZIP-50KIT1	6
TOOL-50-11	Dispensing tool	1
MXR-20T-10	Mixing nozzles	10



To view technical information on our website, go to

[www.polywater.com/zipseal.html](http://www.polywater.com/zipseal.html)

For application videos

[www.polywater.com/videos.asp](http://www.polywater.com/videos.asp)



phone: 1-800-328-9384

1-651-430-2270

fax: 1-651-430-3634

email: [support@polywater.com](mailto:support@polywater.com)

11222 60th Street North, Stillwater, MN 55082, U.S.A.

ADHESIVES | CLEANERS | LUBRICANTS | SEALANTS

[WWW.POLYWATER.COM](http://WWW.POLYWATER.COM)

Important Notice: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.