

PRODUCT OVERVIEW

Fiber Optic Cable Installation Machines

Valid from September 16, 2019



ACCU



ACCU



110/230 V



110/230 V

Model	NanoFlow	NanoFlow MAX	MicroFlow Touch	MicroFlow LOG
Typical Usage	Inside	Inside	Inside	Inside
Fiber/Cable OD	0.8 - 3 mm	0.8 - 4.5 mm	0.8 - 6.5 mm	0.8 - 6.5 mm
Duct Size OD	3 - 10 mm	3 - 12.7 mm	4 - 16 mm	4 - 16 mm
Part no. #	101-160601800	101-190911001	101-10051	101-171001001
Max Speed	150 m/min (490 ft)	125 m/min (410 ft)	90 m/min (295 ft)	90 m/min (295 ft)
Blowing distance	Up to 1200 m (3940 ft)	Up to 1200 m (3940 ft)	Up to 2500 m (8200 ft)	Up to 2500 m (8200 ft)
Rec. Airflow	200 l/min (7.1 cfm)	200 l/min (7.1 cfm)	200 - 500 l/min (7.1 - 17.7 cfm)	200 - 500 l/min (7.1 - 17.7 cfm)
Rec. Pressure	Max. 10 bar air (150 psi)	Max. 10 bar air (150 psi)	8 - 16 bar air (120 - 230 psi)	8 - 16 bar air (120 - 230 psi)
Length Width Height Weight	212 mm 104 mm 139 mm 2.8 kg (w/o battery)	212 mm 104 mm 139 mm 2.8 kg (w/o battery)	Machine: 250 mm Control Box: 200 mm 150 mm 150 mm 220 mm 80 mm 9.7 kg 1.9 kg	Machine: 250 mm Control Box: 240 mm 150 mm 250 mm 220 mm 80 mm 11.3 kg 1.9 kg
Service requirement	Annually	Annually	Annually or every 350000 m	Annually or every 350000 m
Unique features	<ul style="list-style-type: none"> Fully automatic Unique double fiber protection Battery-powered No tools needed 	<ul style="list-style-type: none"> Unique double fiber protection Adjustable clamping force No tools needed Lightweight but powerful 	<ul style="list-style-type: none"> Anti-Buckle Fiber Detection Adjustable Torque Preset Automatic Stop Adjustable Speed Control 	<ul style="list-style-type: none"> Access to OptiCloud Possibility of job documentation & planned maintenance Anti-buckle Fiber Detection




PRODUCT OVERVIEW

Fiber Optic Cable Installation Machines


Valid from September 16, 2019



HYDRAULIC



HYDRAULIC



HYDRAULIC

RELINING

Model	MiniFlow RAPID	PowerFlow	MultiFlow
Typical Usage	Outside	Outside	Outside
Fiber/Cable OD	3 - 12 mm	5.5 - 25 mm	5.5 - 32 mm
Duct Size OD	7 - 20 mm	10 - 63 mm *	10 - 63 mm *
Part no. #	101-10031	101-10001	101-10002
Max Speed	100 m/min (325 ft)	80 m/min (260 ft)	80 m/min (260 ft)
Pushing Force	0 - 40 kg	0 - 125 kg	0 - 200 kg
Blowing distance	Up to 3500 m (11485 ft)	Up to 10000 m (32810 ft)	Up to 10000 m (32810 ft)
Rec. Airflow	1000 l/min (35.3 cfm)	8000 - 12000 l/min (282.5 - 423.8 cfm)	8000 - 12000 l/min (282.5 - 423.8 cfm)
Rec. Pressure	8 - 16 bar air (120 - 230 psi)	8 - 12 bar air (120 - 170 psi)	8 - 12 bar air (120 - 170 psi)
Length	650 mm	650 mm	700 mm
Width	225 mm	230 mm	230 mm
Height	210 mm	350 mm	350 mm
Weight	24 kg	38 kg	40 kg
Service requirement	Annually	Annually	Annually
Unique features	<ul style="list-style-type: none"> • Possible to reverse cable • Flexible adaptability • Adjustable Torque Distance and Speed measurement 	<ul style="list-style-type: none"> • Rugged, solid construction • Flexible adaptability • Adjustable torque distance and speed measurement 	<ul style="list-style-type: none"> • Relining and Single Cable • Rugged Construction • Adjustable Torque Distance and Speed measurement



* Standard duct size OD for PowerFlow and MultiFlow: 14 - 60 mm
 Custom made duct size OD for PowerFlow and MultiFlow: 10 - 13 mm & 60 - 63 mm

